

## Office Lighting

# OFISLED

IP20  
IP40 Optional




LGO



LGO-MP (Micro-Prismatic diffuser)  
Micro-prismatic diffuser creates variable effects according to your point of view

This is a fixture model with a wide usage and application. The light coming from multiple LED sources in LGO fixtures passes through the opal diffuser and provides an extremely soft and homogeneous distribution to the environment. Production for all types of suspended ceilings is possible. Therefore, production is made according to the brand/model of the suspended ceiling to be used. This fixture, like all Litpa fixtures is highly efficient and economical.



	Code	a	b	Cut-Out
MODULAR	LGO 001 30-60	295mm	595mm	280x580mm
	LGO 001 60-60	595mm	595mm	580x580mm
CLIP-IN	LGO 001 30-120	295mm	1195mm	280x1180mm
	LGO 002 30-60	299mm	599mm	-
GYPSUM	LGO 002 60-60	599mm	599mm	-
	LGO 002 30-120	299mm	1199mm	-
MODULAR	LGO 300 30-60	295mm	595mm	-
	LGO 300 60-60	595mm	595mm	-
	LGO 300 30-120	295mm	1195mm	-
	LGO 300 60-120	595mm	1195mm	-

Code	LGO 60/20	LGO 60/30	LGO 60/40	LGO 60/45
LED	High Efficiency Mid-Power LED			
System Power	20 W	30 W	40 W	45 W
Light Flux	2.100 lm	3,300 lm	4,350 lm	4.600 lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	0,5mm thick DKP sheet steel. Frame made of 0,5mm thick DKP steel. 80 micron thick electrostatic powder paint			
Diffuser	Opal			
Cooler	Cooling from the body surface			
Colour	White			
Box Dimensions	65x64x14 cm			
Weight	4.500 gr			

